

Test stand cable was built and labeled assuming columns A-H are correct.

Connector		Wire Color		T-Board				Via Ref Des	
P1 Pin	Cable#	Signal Name	Solid/Band	AWG	Pair	Via Ref Des	Signal Name	For V2.0	For V2.1
1	1	OUT8_P	Red/Black	26	1	W44	SUB1	U	U
16	1	OUT8_N	Black/Red	26	1	W46	GNDa	N	N
2	1	OUT7_P	White/Black	26	2	W18	OUT7_P	C	C
17	1	OUT7_N	Black/White	26	2	W19	OUT7_N	H	H
3	1	OUT6_P	Green/Black	26	3	W14	OUT6_P	A	A
18	1	OUT6_N	Black/Green	26	3	W15	OUT6_N	N	N
4	1	OUT5_P	Blue/Black	26	4	W10	OUT5_P	G	G
19	1	OUT5_N	Black/Blue	26	4	W11	OUT5_N	E	E
5	1	OUT4_P	Yellow/Black	26	5	W7	OUT4_P	D	D
20	1	OUT4_N	Black/Yellow	26	5	W9	OUT4_N		
6	1	OUT3_P	Brown/Black	26	6	W61	OUT3_P	W52	W61
21	1	OUT3_N	Black/Brown	26	6	W62	OUT3_N	W50	W62
7	1	OUT2_P	Orange/Black	26	7	W57	OUT2_P	W54	W58
22	1	OUT2_N	Black/Orange	26	7	W58	OUT2_N	W53	W57
8	1	OUT1_P	White/Red	26	8	W53	OUT1_P	W58	W54
23	1	OUT1_N	Red/White	26	8	W54	OUT1_N	W57	W53
9	2	OUT0_P	Red/Black	26	1	W50	OUT0_P	W61	W52
24	2	OUT0_N	Black/Red	26	1	W52	OUT0_N	W62	W50
10	2	TRG_P	White/Black	26	2	W20	TRG_P		
25	2	TRG_N	Black/White	26	2	W22	TRG_N		
11	2	CLK_P	Green/Black	26	3	W24	CLK_P	U	U
26	2	CLK_N	Black/Green	26	3	W26	CLK_N	N	N
12	2	Bias	Blue/Black	26	4	W3	SUB0	C	C
27	2	Bias_Ret	Black/Blue	26	4	W1	GNDb	H	H
13	2	VSS_SENSE	Yellow/Black	26	5	W16	VSSb_sense	A	A
28	2	GND_SENSE_VS	Black/Yellow	26	5	W17	GNDb_sense	N	N
14	2	VDD_SENSE	Brown/Black	26	6	W12	VDDb_sense	G	G
29	2	ND_SENSE_VD	Black/Brown	26	6	W13	GNDb_sense	E	E
37	2	SCLK_VSS	Black/Orange	26	7	W40	VSS_CLKb	D	D
38	2	SCLK	Orange/Black	26	7	W37	SCLKb		
39	2	SDA_VSS	Red/White	26	8	W36	VSS_SDAb		
40	2	SDA	White/Red	26	8	W41	SDAb		
15	3	VDD	Red	22	N/A	W5	VDDb		
30	3	GND	Black	22	N/A	W4	GNDb		
41	3	GND/SHD	Silver Drain Wire	22	N/A	W2	GNDb		
43	3	VSS	White	22	N/A	W6	VSSb		
44	3	VSS	Green	22	N/A	W8	VSSb		

U
N
C
H
A
N
G
E
D

U
N
C
H
A
N
G
E
D