

MOLD COOLING

MoldBasics® SV-Series Hose Connectors

SV-Series Male Plugs* – NS

(Automatic Shut-Off Type with Stemmed Valve)



SOCKET

PLUG

**The SV-Series Male Plugs operate only with the SV-Series Sockets. All SV-Series Male Plugs are supplied with Viton seals for use in water, air and heat transfer oil applications that do not exceed 400°F and 200 psi.

DESCRIPTION	LENGTH L	PIPE THREAD	Ø HOLE	HEX SIZE	ITEM NUMBER	USED WITH SOCKETS*
 (BRASS)	1 ¹ / ₂	¼ NPT	¼	9/ ₁₆	NS252SV	NS204SV to NS226SV
	1 ³ / ₁₆	¾ NPT	¼	11/ ₁₆	NS253SV	
	1 ² / ₆₄	¼ NPT	3/ ₈	9/ ₁₆	NS352SV	NS306SV to NS328SV
	1 ² / ₆₄	¾ NPT	3/ ₈	11/ ₁₆	NS353SV	
	1 ³ / ₆₄	½ NPT	3/ ₈	7/ ₈	NS354SV	

SV-Series Sockets – NS

(Automatic Shut-Off Type with Stemmed Valve)

DESCRIPTION	ITEM NUMBER	FITS HOSE I.D. OR PIPE THREAD	HOSE STEM I.D. OR THRU HOLE	USED WITH SV-MALE, STD MALE, FEMALE OR EXTENSION PLUGS
 STRAIGHT STEM	NS204SV	¼	¼	NS250 TO 253 (SV) (FB)
	NS205SV	5/ ₁₆	¼	NS250 TO 253 (SV) (FB)
	NS206SV	3/ ₈	¼	NS250 TO 253 (SV) (FB)
	NS306SV	3/ ₈	3/ ₈	NS351 TO 354 (SV) (FB)
	NS308SV	½	3/ ₈	NS351 TO 354 (SV) (FB)
 90° STEM	NS214SV	¼	¼	NS250 TO 253 (SV) (FB)
	NS215SV	5/ ₁₆	¼	NS250 TO 253 (SV) (FB)
	NS216SV	3/ ₈	¼	NS250 TO 253 (SV) (FB)
	NS316SV	3/ ₈	3/ ₈	NS351 TO 354 (SV) (FB)
	NS318SV	½	3/ ₈	NS351 TO 354 (SV) (FB)
 45° STEM	NS224SV	¼	¼	NS250 TO 253 (SV) (FB)
	NS225SV	5/ ₁₆	¼	NS250 TO 253 (SV) (FB)
	NS226SV	3/ ₈	¼	NS250 TO 253 (SV) (FB)
	NS326SV	3/ ₈	¼	NS351 TO 354 (SV) (FB)
	NS328SV	½	3/ ₈	NS351 TO 354 (SV) (FB)
 FEMALE NPT THREAD	NS200SV	¼ NPT	¼	NS250 TO 253 (SV) (FB)
	NS300SV	¾ NPT	3/ ₈	NS351 TO 354 (SV) (FB)
 MALE NPT THREAD	NS201MSV	¼ NPT	¼	NS250 TO 253 (SV) (FB)
	NS302MSV	¼ NPT	3/ ₈	NS351 TO 354 (SV) (FB)

90° and 45° NPT Elbows

(For Female and Male NPT Sockets Only)

DESCRIPTION	ITEM NUMBER	PIPE THREAD	THRU HOLE	USED WITH SOCKETS
 45° NPT ELBOW	BE4S2-2	¼ NPT	7/ ₃₂	NS200 (V/SV) TO NS201M (V/SV)
	BE4S4-4	¼ NPT	5/ ₁₆	NS300 (V/SV) TO NS302M (V/SV)
	BE4S8-8	½ NPT	9/ ₁₆	NS500 (V) TO NS504M (V)
 90° NPT ELBOW	BE9S2-2	¼ NPT	7/ ₃₂	NS200 (V/SV) TO NS201M (V/SV)
	BE9S4-4	¼ NPT	5/ ₁₆	NS300 (V/SV) TO NS302M (V/SV)
	BE9S8-8*	1/2 NPT	9/ ₁₆	NS500 to NS504M (V)

These 90° and 45° NPT elbows can be used with either V or SV, female or male NPT sockets only.

QUANTITY DISCOUNTS: MoldBasics® Sockets or Plugs. Discounts apply to current Net Prices. See List Price Adjustment. Standard sizes may be combined on one order for quantity discounts. 100 to 499...Less 3%; 500 or more...Less 6%